



TapeCase Ltd.
1982 Lunt Rd
Elk Grove Village, IL 60007
phone: (847) 299-7880
fax: (847) 299-7804
www.tapecase.com
sales@tapecase.com

TC1008-Paper Tape

Technical Data

Product Description – A medium tack paper application tape for vinyl graphics used in sign making and surface protection. The product consists of a self-wound, standard grade saturated backing coated with a specially formulated latex pressure sensitive adhesive.

Product Characteristics Construction

Backing	White translucent latex saturated paper
Adhesive	Water based natural latex
Total Thickness	4 mil (nominal)

Performance

Tensile Strength (pli)	MD 20
Elongation (%)	2.4
Average Adhesion (oz/in)	180° Peel @ time of manufacture
PSTC	#4 bright annealed stainless steel 11.0

The physical properties listed above are typical values and are not to be considered as specifications. Our suggestions for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for their internal use. TapeCase assumes no liability for claims beyond those outlined within our Limited Warranty, which includes replacement value of TapeCase product proven defective. For full disclosure of the Limited Warranty, please contact your TapeCase representative.

Typical Uses - Excellent for medium and large plotter and die-cut graphics. Works well with pre-spaced lettering 2-12", small one piece decals and mid-sized line striping.