



Repulpable Double-Coated Web Splicing Tape

9038B • 9038W

Technical Data

Product Description 3M™ Repulpable Double-Coated Web Splicing Tapes 9038B and 9038W are a light-weight tissue coated on both sides with a high tack, high shear strength, repulpable adhesive and are furnished on a repulpable easy-release paper liner. Available in blue and white tape.

Product Construction	Product	Backing	Color	Standard Roll Length
	3M tape 9038B	Silicone-coated, semi-bleached kraft paper	Blue	36 yds. (33 m)
	3M tape 9038W	Silicone-coated, semi-bleached kraft paper	White	36 yds. (33 m)

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Repulpability:	Tape – Completely* Liner – Completely*
Tape Thickness:	3 mils (0.075 mm)
Bonding Strength:	Delaminates most papers
Heat Resistance:	Excellent to 400°F (204°C) web temperature

*Repulpability judged according to TAPPI UM-213, Procedure A. It is important to follow the weight and quantity measurements for the fiber, splicing tape and water. Non-representative results can occur if test guidelines are not followed.

Features

- Packing in sealed plastic bags helps assure constant moisture content of unused tape.
- Virtually eliminates the human element from flying splice adhesive operations. There are no “drying times,” “correct mixtures,” “too soft,” “too wet,” etc. which depend on operator performance or judgements.
- Water solubility and alkali dispersability are excellent and eliminate danger of contaminating the paper mill broke with non-repulpable material. (Poor quality paper and plugged Fourdrinier screens often can be caused by typical non-repulpable rubber base splicing media.)
- Not recommended for finished roll splices or where oozing and bleeding may occur.

Application Techniques

For optimum results, firm even rub down pressure must be applied to the taped area to create the best possible adhesion between the tape and paper surface. A plastic squeegee or similar tool can help achieve the proper uniform pressure.

3M™ Repulpable Double-Coated Web Splicing Tape

9038B • 9038W

Application Ideas

- Splicing tape for manual and automatic splicing equipment.

Storage

Store under normal conditions of 70°F (21°C) and 50% R.H. in the original carton.

Shelf Life

To obtain best performance, use this product within 18 months from date of manufacture.

Product Use

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy

Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability

Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001:2000

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2000 standards.

3M

Industrial Business Industrial Adhesives and Tapes Division

3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (fax)
www.3M.com/industrial



Recycled Paper
40% pre-consumer
10% post-consumer

Printed in U.S.A.
©3M 70-0709-4463-5 (1999/6/05)