



TapeCase Ltd.
150 Gaylord Street
Elk Grove Village IL 60007
phone: (847) 299-7880
fax: (847) 299-7804
www.tapecase.com

SPVC Vinyl Colored Tape

SSS-625

General Description

"Physical Hazard/Caution" tape. 6 mil conformable soft PVC vinyl. Synthetic rubber adhesive. Self-extinguishing. Striping and warning. Mark hazardous areas to comply with OSHA requirements per paragraph 1910.144 of the federal register. Supplied on 3" core.

Product Benefits

Product is of superior quality, with a long shelf-life, and "write-on" capability. It provides a very effective vapor and moisture barrier. It is highly conformable and resistant to aging, sun, water, fungus, bacteria, oil, acids, alkalies and corrosive chemicals. It provides good abrasion, impact and rupture resistance.

Technical Data

TECHNICAL PROPERTIES	
Backing	Conformable Soft PVC Vinyl
Adhesive	Rubber-based synthetic
Total Thickness	6 mil (0.15mm)
Adhesion to Steel	13.7 oz/in.
Tensile Strength	15 lbs/in.
Temperature Resistance	14° F - 176° F
Elongation	210% at break

5 OSHA Colors: Black/Yellow, Red/White, Black/White, Green/White & Magenta/Yellow.

NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. Shelf life is one year from date of shipment when stored in a cool dry place below 76° F (24°C). Rolls should be stored on end.
3. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.