



TapeCase Ltd.
150 Gaylord St, Elk Grove Village, IL 60007
phone: (847) 299-7880
fax: (847) 299-7804
www.tapecase.com
sales@tapecase.com

Printed White Water Activated Carton Sealing Tape

150KPT-1-WHITE “WARNING”

150KPT-2-WHITE “FRAGILE”

Product Description

Light Duty Reinforced Water Activated Tape is used for box sealing and other packaging applications. This product has a fiberglass reinforced paper backing and a high tack water-activated adhesive system.

Applications

- Recommended for sealing packages weighing a maximum of 30 lbs
- Used for two C clips on cartons – top and bottom.
- Works well on recycled cartons and non-unitized loads.
- Construction assures a reliable performance in a range of environments and applications.

Product Construction

Top Sheet:	Tape: 30 lbs/ream Bleached Virgin Kraft
Bottom Sheet:	23 lbs/ream MG Natural High Strength Virgin Kraft
Laminating Matl:	Polypropylene based polymer
Reinforcement:	3 Way Fiber Glass Reinforcing Pattern <ul style="list-style-type: none">• Pattern: Lengthwise threads with diamond cross-machine pattern• Lengthwise Threads: 110 Denier Fiberglass -5/8" Spacing (1-1-1-1-1)• Cross Machine Threads: 150 Denier Fiberglass–Diamond Pattern less than 1-1/4" spacing between threads
Tensile Strength (lbs/inch):	Machine Direction: 52-57 Cross Direction: 24-29
Adhesive:	High Tack, Water Activated, modified Starch Based Adhesive
Caliper:	7.3 mils

NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers..
2. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.