



TapeCase Ltd.
150 Gaylord Street
Elk Grove Village, IL 60007
phone: (847) 299-7880
fax: (847) 299-7804
www.tapecase.com
sales@tapecase.com

Silicone Splicing, Placement Holding Tape

TC573- Blue

General Description

A self-wound 1mil polyester film, coated on one side with a high tack translucent blue silicone adhesive. Great for splicing applications low surface energy films such as release liners...Also a great choice for use as a placement/holding tape that may require clean removal.

Product Benefits

- Good temperature range
- Good Tack
- High Peel
- Bonds to low energy surfaces

Technical Data

TECHNICAL PROPERTIES	
Total Thickness	2.5 mil
Temperature Range	-65°F to +400°F
Color	Translucent Blue

ADHESIVE TEST DATA	
Peel Adhesion to Stainless Steel	30 oz./in
Adhesive	1.4 mil Silicone
Backing	1mil Polyester

NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. Shelf life is one year from date of shipment when stored in a cool dry place below 76° F (24°C). Rolls should be stored on end.
3. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.