

## TapeCase Ltd.

150 Gaylord St, Elk Grove Village, IL 60007

phone: (847) 299-7880 fax: (847) 299-7804 www.tapecase.com sales@tapecase.com

# Valeron Tape

#### **Product Description**

Brilliant white high performance Valeron Tape features a versatile acrylic adhesive. The glossy white backing adds a high end finish to almost any surface. It's appearance is almost white board like. The Valeron backing is extremely durable and ideal for applications that require a product that cannot be torn or ripped.

#### **Applications**

Finishing tape for banners and signage for outdoor use Decorative Trim and Borders Seaming and Sealing

### **Typical Physical Properties**

Total Thickness	11.7 mils
Adhesive Thickness	3 mils
Adhesive Type	Acrylic
Backing Thickness	8.7 mils
Backing Material	HDPE Blend

#### **Adhesive Test Data**

ADHESIVE TEST DATA	
Adhesion to Steel	75 oz./in
Tensile Strength	90 lbs/in
Operating Temperature	-32°F to 250°F
Application Temperature	40°F to 150°F

#### NOTE:

<sup>1.</sup> When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminates such as powder, dust or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers..

substrates containing plasticizers..

2. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.