



TapeCase Ltd.
1982 Lunt Rd
Elk Grove Village, IL 60007
phone: (847) 299-7880
fax: (847) 299-7804
www.tapecase.com
sales@tapecase.com

Single Coated Polyethylene Tape

133

General Description

133 is a polyethylene film, single coated with a rubber pressure sensitive adhesive. This tape has a low residue aggressive adhesive. It bonds well to most surfaces over a wide temperature range. It has serrated edges for easy tearing

Applications

- Polyethylene splicing
- Surface protection
- Industrial assembly applications

Technical Data

TECHNICAL PROPERTIES	
Total Thickness	7.5 mil
Adhesive Thickness	3.0 mil

ADHESIVE TEST DATA	
Peel Adhesion	70 oz./inch (19 N/25mm)
Backing Adhesion	35 oz./inch (9.6 N/25mm)
Tensile Strength	22 lbs./inch (96 N/25mm)
Elongation	100%

NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. Shelf life is one year from date of shipment when stored in a cool dry place below 76° F (24°C). Rolls should be stored on end.
3. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.