



TapeCase Ltd.
150 Gaylord Street, Elk Grove Village, IL 60007
phone: (847) 299-7880
fax: (847) 299-7804
www.tapecase.com
sales@tapecase.com

TC602 - COLORED CREPE PAPER MASKING TAPE

GENERAL DESCRIPTION

TC602 is a line of colored, general purpose grade masking tape with a synthetic rubber adhesive system. Tape adheres to a variety of surfaces. Designed for general purpose applications where color-coding for identification, labeling or decorating is desired. Suitable for light duty applications such as bundling, sealing, marking of defective parts or materials, inventory item maintenance, splicing, banding etc. Also used for produce marking and polybag sealing. Not to be used at temperatures exceeding 150°F.

Meets LHAMA requirements for use in arts and crafts and ASTM D 6123/D 6123M-97 (2012), Type I; Meets Consumer Product Safety Commission requirements through conformance with ASTM D-4236.

STORAGE TEMPERATURE & SHELF LIFE:

Tape should be stored in a cool, dry area (~60% RH) at temperatures of 60°F to 80°F. If stored appropriately, tape has a shelf life of 1 year from date of manufacture.

PHYSICAL PROPERTIES

Backing	Colored Crepe Paper
Adhesion	34 oz/inch
Total Thickness	4.9 mil
Tensile Strength	20 lb/inch
Elongation at break	9%
Temperature Range	not to exceed 150°F
Colors	Red, White, Lt Blue, Lt Green, Dk Green, Black, Orange & Yellow

NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.