



TapeCase Ltd.
150 Gaylord Street
Elk Grove Village, IL 60007
phone: (847) 299-7880
fax: (847) 299-7804
www.tapecase.com
sales@tapecase.com

UV Resistant Polyethylene Surface Protection Tape UV-PRO

General Description

A low to medium tack masking tape for use in exterior applications. The product consists of a self-wound, low density polyethylene film in clear or blue, with ultraviolet inhibitor. 2U01 is coated with a custom formulated water based acrylic adhesive for outdoor environmental performance.

Applications

Excellent performance as a window masking with UV resistance and outdoor exposure up to 90 days. Suitable for masking and protection of smooth metals including bright annealed stainless steel, high gloss painted metals, anodized bright aluminum and polished aluminum.

Technical Data

TECHNICAL PROPERTIES	
Thickness	2 mil
Tensile Strength	MD 2800 / TD 2450
Elongation	MD 325 / TD 2450
Adhesion Range	2.5 (oz./in)

NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. Shelf life is one year from date of shipment when stored in a cool dry place below 76° F (24°C). Rolls should be stored on end.
3. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.