



TapeCase Ltd.  
1982 Lunt Ave, Elk Grove Village, IL 60007  
phone: (847) 299-7880  
fax: (847) 299-7804  
www.tapecase.com  
sales@tapecase.com

## Cloth Friction Tape TC157

### GENERAL DESCRIPTION

TC157 consists of a scientifically compounded pure rubber based adhesive which has been properly calendared and impregnated into high grade cotton cloth. This tape is commonly used for over wrapping low voltage splices, harnessing and cover taping for many mechanical applications.

### FEATURES

Friction tape with a superior strength and is resistant to abrasion and moisture. TC157 has a high percentage of pure rubber for maximum elasticity and moisture resistance. Does not fray or unravel.

**Meets ASTM 4514-85. This product is ROHS compliant.**

### AVAILABLE SIZES

3/4" X 30'

3/4" X 60'

3/4" X 82.5'

TECHNICAL PROPERTIES	
Insulation Class	80°C
Color	Black
Adhesive	Rubber Resin
Total Thickness	15 mils
Tensile Strength	42lbs/in
Backing	Cotton Cloth
Adhesion	14 lbs/in
Elongation	8%
Dielectric Strength	1000 volt

### Comparable: 3M 1755 and Plymouth 1002, 1004, 1006 (100ASTM)

#### NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. Shelf life is one year from date of shipment when stored in a cool dry place below 76° F (24°C). Rolls should be stored on end.
3. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.