

TapeCase, Ltd

1982 Lunt Ave, Elk Grove Village, IL 60007 • PHONE (847) 299-7880 • FAX (847) 299-7804

PRODUCT DATA

TC-FSK

ALUMINUM FOIL / SCRIM / KRAFT TAPE

w/ Synthetic Rubber

TC-FSK is a three way dead soft malleable Aluminum Foil / fiberglass scrim / paper coated with an aggressive Synthetic Rubber pressure sensitive adhesive carried on a removable paper release liner.

FEATURES/BENEFITS:

This tape is conformable and maximizes adhesive contact to insulation surface. Aggressive adhesive provides quick, positive grab to insulation surface. Malleable foil conforms well to irregular & curved surfaces.

APPLICATIONS:

- Used as a closure system for fiberglass and mineral wool insulation systems that are faced with foil
- Used to seal seams and joints on aluminum faced fiberglass duct board
- Used to provide a vapor barrier that assures the integrity of the system

PHYSICAL PROPERTIES*:

Adhesive	Rubber Resin Adhesive
Foil-Scrim-Kraft backing	4.8 mil
Total Thickness (Backing + Adhesive)	6.8 mil
Peel Adhesion	90 oz/inch
Rolling Tack (11mm ball)	8 inch.
Service Temperature	-4°F to 176 °F

SURFACE PREPARATION:

The surface to which the tape is applied should be dry, clean, and free of grease and oil.

STORAGE TEMPERATURE:

Tape should be stored at room temperature and kept from wet and keep away heat source.

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.