



TapeCase Ltd.  
420 Northgate Parkway, Wheeling, IL 60090  
phone: (847) 299-7880  
fax: (847) 299-7804  
[www.tapecase.com](http://www.tapecase.com)  
[sales@tapecase.com](mailto:sales@tapecase.com)

# TC4001-302CL

## Clear Protective Film Tape

### Product Description

---

TC4001-302CL is a high tack protective masking tape for use in surface protection. The product consists of a low density polyethylene self-wound film, coated with a custom formulated water based acrylic adhesive with a soft release.

### Features

---

- Backing - Low-Density Polyethylene
- Adhesive - Water-Based Acrylic, Soft-Release

### Technical Properties

---

TECHNICAL PROPERTIES	
Thickness	4.0 mil
Thickness Tolerance	Nominal
Tensile Strength (psi)	3300 psi
Elongation	500% to 550%

### Application and Storage

---

**NOTE:**

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. Shelf life is one year from date of shipment when stored in a cool dry place below 76° F (24°C). Rolls should be stored on end.
3. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.