



TapeCase Ltd.
1982 Lunt Ave, Elk Grove Village, IL 60007
phone: (847) 299-7880
fax: (847) 299-7804
www.tapecase.com
sales@tapecase.com

Glow in the Dark Marking Tape

7520 Series

Product Description

7520 is a flexible laminated, printed film that is perfect for marking pathway obstructions that may be hazardous in blackout and very smoky conditions. This tape absorbs and stores energy from ambient light, and is immediately visible in sudden darkness. 7520 easily affixes to most wood, metal, concrete, plaster and painted surfaces. Incomparably reliable, 7520 is perfect for your low-level emergency egress system.

Product Construction

Flexible laminated, printed film coated with permanent acrylic pressure-sensitive adhesive and backed by poly-coated release liner.

Typical Properties

Property	Characteristic
Thickness	0.012 +/- 10% (film/adhesive)
Color	White/Green with Red, Green or Black striping (normal light conditions)
Illumination	High Visibility Yellow/Green
UV Stability	Excellent
Installation	Position, peel-off backing and apply to dry, non oily surface. Minimum application temperature is 50°F

NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes