



TapeCase Ltd.
1982 Lunt Ave, Elk Grove Village, IL 60007
phone: (847) 299-7880
fax: (847) 299-7804
www.tapecase.com
sales@tapecase.com

Flatback Paper Tape

TC534

Product Description

Considered by many as the “Industry Standard”. A moisture resistant flatback tape with an aggressive natural / synthetic rubber pressure sensitive adhesive designed to offer a positive, attractive seal and excellent adhesion to minimize carton sealing failures and prevent pilferage. Having an excellent balance of machine and cross-direction tensile and tear strength, TC534 remains strong under moist conditions. Excellent for many splicing needs. Product is approved as packaging tape by both U.S. Postal Service and U.P.S (United Parcel Service). **Product is not repulpable.**

Applications

- Carton sealing / packaging
- Silk screening
- Picture framing
- Beaming / Leasing
- Splicing and tabbing

Typical Physical Properties

Property	Characteristic
Backing Material	Kraft Flatback
Mil Thickness	7.2
Adhesive System	Natural / Synthetic Rubber
Adhesion (oz/in)	43
Tensile Strength (lb/in)	35
Elongation (%)	8
Color	Brown
Temperature Resistance (F)	Application: 50° to 120° Operating: 32° to 180°
Specification Conformance	PPP-T-42C, Type II C.I.D. A-A-883, Type II

NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. The above values are “Typical Values” which have a nominal range about them and are not intended for specification purposes