



TapeCase Ltd.  
420 Northgate Parkway, Wheeling, IL 60090  
phone: (847) 299-7880  
fax: (847) 299-7804  
www.tapecase.com  
sales@tapecase.com

# TC4150

## Ultra High Tack Silicone Splicing

### Product Description

---

Splicing release coated surfaces and liners. A conformable, high strength, low profile splicing tape for various films and labels. Also an excellent plating tape for printed circuit boards.

### Features

---

- Ultra high tack
- High temp resistance
- Chemical resistance

### Technical Properties

---

Color	Yellow
Total Thickness	2.9 mil
Backing	1 mil Polyester
Adhesive	1.9 mil Silicone
180° Peel Adhesion to Stainless Steel	48 oz/in
Temperature Range	-65°F to 400°F

### Application and Storage

---

*Note: The physical and performance characteristics shown are averages obtained from tests performed according to ASTM and PSTC test methods. TapeCase can make no warranty of any kind as to the results of the adhesive product used. The information published here is representative of laboratory research on these products and is believed to be reliable. Values should not be used for specification purposes. Each user should make their own test to determine the product's suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.*