



TapeCase Ltd.  
150 Gaylord Street  
Elk Grove Village, IL 60007  
phone: (847) 299-7880  
fax: (847) 299-7804  
www.tapecase.com  
sales@tapecase.com

## TC120109 14 Mil Black Woven Polyethylene Tape

### Product Description:

SC231210-140 consists of a woven polyethylene coated on one side with a high tack, high peel, and moderate shear repositionable pressure sensitive adhesive. This product offers excellent puncture, tear, and moisture resistance. The SC231210-140 is typically used as a tarp repair tape or bottom board barrier tape.

Features / Benefits:	Applications:	Construction:
- Great Tack & Peel - Puncture & Tear Resistant - Moisture Resistant - Performs in a Wide Temperature Range	- Bottom Board Tape - Tarp Repair - Moisture Barrier Tape	<i>Type: Single Coated Woven PE Tape</i> <i>Carrier: Woven Polyethylene</i> <i>Adhesive Type: Synthetic Rubber</i> <i>Liner: SCK Liner</i>

### Physical Characteristics:

Product Number	Color	Peel Adhesion	Loop Tack	Shear Adhesion	Liner	Operating Temperature (°F)
TC120109	Black	90 Oz / Inch	63 Oz / Inch	24 + Hours	60# CIS SCK	+0 to +160

#### NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. Shelf life is one year from date of shipment when stored in a cool dry place below 76° F (24°C). Rolls should be stored on end.
3. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.