



TapeCase Ltd.
150 Gaylord St, Elk Grove Village, IL 60007
phone: (847) 299-7880
fax: (847) 299-7804
www.tapecase.com
sales@tapecase.com

Clear Polywoven Tape

Product Description

High performance, high strength reinforcement tape used as to repair, seaming, patch, reinforce and seal a number of substrates. Backing of tape appears tarp like and has an aggressive acrylic adhesive backing making it suitable to use indoors and out.

Applications

- Tarp Repair
- Patio Furniture Patch/Repair
- Bundling
- Signage Hem Reinforcement
- Tent patch
- Bag Repair

Typical Physical Properties

Total Thickness	14 mils
Adhesive Thickness	3 mils
Adhesive Type	Acrylic
Backing Thickness	11 mils
Backing Material	HDPE Blend

Adhesive Test Data

ADHESIVE TEST DATA	
Adhesion to Steel	68 oz./in
Tensile Strength	75 lbs/in
Operating Temperature	-32°F to 250°F
Application Temperature	40°F to 150°F

NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers..
2. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.