



TapeCase Ltd.
150 Gaylord Street, Elk Grove Village IL 60007
phone: (847) 299-7880
fax: (847) 299-7804
www.tapecase.com
sales@tapecase.com

Contractor Grade Duct Tape

TC600

General Description

For general purpose use in industrial, carpet, plumbing, packaging and masking in HVAC, sealing, waterproofing, patching, remediation and restoration applications

PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	22 lbs/in width	38.5 N/10 mm
Adhesion to Stainless Steel	55 oz/in width	6.02 N/10 mm
Thickness	9 mils	0.23 mm
Elongation	16%	16%
Service Temperature Range	32 F to 200 F	0 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

PRODUCT FEATURES

- Conformable
- Will not twist or curl during application
- Hand-tearable
- Made using Polybonded CO-EX Technology®

CONSTRUCTION

Overall Grade/Function: Contractor

Backing: Waterproof polyethylene film with a cloth carrier

Adhesive: Natural rubber

APPLICABLE STANDARDS

Meets Consumer Product Safety Commission requirements through conformance with ASTM D-4236

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.
3. Under moderate conditions, cohesive films will have up to a six-month shelf life.