

TapeCase Ltd.

1982 Lunt Ave, Elk Grove Village, IL 60007

phone: (847) 299-7880 fax: (847) 299-7804 www.tapecase.com sales@tapecase.com

Clean Release Polyethylene Surface Protection Tape TC3001

Product Description

3001-302CL is low tack masking tape use for in surface protection. This product consists of a low-density Polyethylene backing, coated with a custom formulated water based acrylic adhesive with a soft release.

Product Construction

Backing- Low-Density Polyethylene

Adhesive- Water-Based Acrylic, Soft-Release

Product Characteristics

| Property | Characteristic | Test Method |
|--|----------------|--------------------|
| Thickness (mil) | 3.0 Nominal | N/A |
| Tensile Strength (psi) | MD 3800 | ASTM D 882 |
| | TD 3000 | ASTM D 882 |
| Elongation (%) | MD 470 | ASTM D 882 |
| | TD 650 | ASTM D 882 |
| Adhesion to PSTC Stainless Steel (oz/in) | 3-6 | PSTC-1 |

Shelf Life

Shelf life is one year from date of shipment when stored in a cool dry place below 76°F (24°C). Rolls should be stored on end.

NOTE:

- 1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminates such as powder, dust or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers..
- 2. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.