



TapeCase Ltd.
150 Gaylord St, Elk Grove Village, IL 60007
phone: (847) 299-7880
fax: (847) 299-7804
www.tapecase.com
sales@tapecase.com

PRODUCT DATA SHEET

TCNST

ANTI-SLIP / NON-SKID SAFETY TAPE

General Description

NST-20, "Sure-Step" has an aggressive adhesive, which conforms to irregular surfaces. PVC surface is impregnated with silicone carbide (black) or aluminum oxide (colors) to provide a high traction, anti-slip, waterproof surface.

Applications

For use indoors or outdoors; on walkways, ramps, stairways, in machine shops, work areas, etc.; to comply with OSHA 1910.263(3).

PHYSICAL PROPERTIES:

Tape Thickness	(GRIT NO.60) 0.8 ± 0.2mm
Base Material	PVC Sheet
Liner Type	White Siliconized Paper
Type of Adhesive	Acrylic
Adhesion to Steel	1500g / 25mm ↑
Tensile Strength	6.0KG / 25mm ↑
Elongation at Break	25 % ↑
Temperature Range	- 5°C to 50°C (23°F to 122°F)
General Grit Type	Aluminum Oxide (Colors) Silicone Carbide (Black)
General Grit Size	60 - 70
Resistance to	Water Good
International Standard Quality Assurance System	Passed ISO 9001 / CNS 12682

NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. Shelf life is one year from date of shipment when stored in a cool dry place below 76° F (24°C). Rolls should be stored on end.
3. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.