

VHB TAPES

Strong, durable, and reliable bonding tape

VHB tapes are a strong and durable tape used to attach a variety of substrates together to make finished goods. On top of replacing welds, screws, bolts, and rivets, VHB tapes also have the ability to withstand high and low temperatures, along with UV light, moisture, liquid, and solvents.

Whether you're attaching or mounting substrates together, TapeCase has a wide variety of VHB tapes in different sizes for all your projects needs.



Series	Color	Liner	Adhesive	Thickness (Mil)	Temp. Resistance (30 Min)	Common Applications
4611 Tape Family						
4611	Dark Gray	Red Polyethylene Film	General Purpose Acrylic	45	450 ° F	<ul style="list-style-type: none"> Pre-powder coat paint Channel & stiffeners Decorative materials
4646				25		
4910 Tape Family						
4905	Clear	Red Printed Polyethylene Film	General Purpose Acrylic	20	300 ° F	<ul style="list-style-type: none"> Translucent signs Resin filled glass
4910				40		
4941 Tape Family						
4979F	Black	Red Printed Polyethylene Film	Multi-Purpose Acrylic	62	300 ° F	<ul style="list-style-type: none"> Plastic windows to control panels Vinyl wiring ducts & conduit channels
4945 Tape Family						
4945	White	54# Densified Kraft Paper	Multi-Purpose Acrylic	45	300 ° F	<ul style="list-style-type: none"> Vinyl trim & vinyl extrusions
4950 Tape Family						
4920	White	54# Densified Kraft Paper	General Purpose Acrylic	15	300 ° F	<ul style="list-style-type: none"> Office furniture Stiffeners in AC Unit Telecommunications equipment
4930				25		
4950				45		
4955		Polyester Film		80	400 ° F	
4959				120		
4951 Tape Family						
4951	White	Polyester Film	Low Temp Acrylic	45	300 ° F	<ul style="list-style-type: none"> Low temp installed products
4952 Tape Family						
4932	White	54# Densified Kraft Paper	LSE Acrylic	25	200 ° F	<ul style="list-style-type: none"> Polyethylene & polypropylene Powder coated paints
4952				45		

Series	Color	Liner	Adhesive	Thickness (Mil)	Temp. Resistance (30 Min)	Common Applications	
5952 Tape Family							
5906	Black	Clear Polyethylene Film	Modified Acrylic	6	300 ° F	<ul style="list-style-type: none"> · Lens & touch panel · Logo attachment · P.O.P & display construction · Polycarbonate lens over LCD 	
5907				8			
5908				10			
5909				12			
5915		Red Printed Polyethylene Film		16		<ul style="list-style-type: none"> · Plastic & paint systems · Architectural signs to frames · Trim & extrusions · Hat channels & stiffeners 	
5925				25			
5952				45			
5962				62			
5958FR				40			<ul style="list-style-type: none"> · Signage, plastic, metals, mirror mounting, clip attachment
LSE Tape Family							
LSE-060WF	White	Red Printed Polyethylene Film	LSE Acrylic	25	300 ° F	<ul style="list-style-type: none"> · Signage, lighting, windows · RV, vans, buses, & trucking · Sensors, cameras, appliances 	
LSE-110WF				45			
LSE-160WF				62			
GPH Tape Family							
GPH-060GF	Gray	Red Printed Polyethylene Film	Modified Acrylic	25	450 ° F	<ul style="list-style-type: none"> · Powder coat & liquid painting · High temp 	
GPH-110GF				45			
GPH-160GF				62			
100MP Adhesive Transfer Tape Family							
F9460PC	Clear	58# Polycoated Kraft Paper	High Performance Acrylic	2	500 ° F	<ul style="list-style-type: none"> · High temp autoclaves · Kick-plates · Nameplates · Air bag inflater · LED taillights 	
F9469PC				5			
F9473PC				10			

* Thickness does not include liner