



TapeCase Ltd.
1982 Lunt Ave, Elk Grove Village, IL 60007
phone: (847) 299-7880
fax: (847) 299-7804
www.tapecase.com
sales@tapecase.com

GLO-Brite® 7550

General Description

Using the latest photoluminescent technology, Glo Brite® Tape is a flexible laminated film that absorbs and stores energy from ambient light. In the event of a power outage this tape is immediately visible, providing people with a clearly illuminated evacuation route. Because Glo Brite® Tape easily affixes to walls, handrails, columns, around doorframes, and along stairways and baseboards, it is ideal for your low-level emergency egress system.

Technical Data

| TECHNICAL PROPERTIES | |
|----------------------|--|
| Construction | Flexible laminated film, coated with permanent acrylic pressure-sensitive adhesive and backed by poly-coated release liner |
| Adhesive | Acrylic |
| Thickness | .010 +/- 10% (film/adhesive) |
| Color | White/Green (normal light conditions) |
| Illumination | High Visibility Yellow/Green |
| UV Stability | Excellent |
| Installation | Position, peel-off backing and apply to dry, non-oily surface Minimum application temperature 50° F |

NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purpose