



TapeCase Ltd.  
150 Gaylord St, Elk Grove Village, IL 60007  
phone: (847) 299-7880  
fax: (847) 299-7804  
www.tapecase.com  
sales@tapecase.com

---

# TC3001-042

## Clear Protective Film Tape

### Product Description

---

3001-042 is low tack masking tape use for in surface protection. This product consists of a low-density Polyethylene backing, coated with a custom formulated water based acrylic adhesive with a soft release.

### Features

---

- Backing - Low-Density Polyethylene
- Adhesive - Water-Based Acrylic, Soft-Release

### Technical Properties

---

TECHNICAL PROPERTIES	
Thickness	3.0 (nominal)
Tensile Strength	MD 3800 / TD 3000
Elongation	MD 470 / TD 650
Adhesion to PSTC Stainless Steel	3-6 (oz./in)

### Application and Storage

---

**NOTE:**

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. Shelf life is one year from date of shipment when stored in a cool dry place below 76° F (24°C). Rolls should be stored on end.
3. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.